HSAJET-HP



Image Maker Printing Systems

High resolution ink jet printing for industrial marking and coding

Tomorrows Technology Today

HSAJET HP

Image Maker Printing System

Industrial High Resolution Ink Jet Printer

Controller

- Chassis: Stainless Steel
- Filtered Air Inlet
- 256 MB Ram
- 40 GB hard drive
- Pentium Processor
- Windows 2000
- 4 USB ports
- 10/100 Ethernet standard
- RS232 input
- Voltage: I20 VAC
- Floppy disk: Optional
- One Encoder and Photocell port
- Controls from 1 to 12 stalls*

Resolution and Character Size

- 600, 300, 150, 75 DPI
- Max character size from one stall is 0.5"
- Max print height per driver card is 52.8 mm*
- Max stalls is 12 or 6" of print

Environment

- Operating temperature 40°F -104°F (5°C - 40°C)
- Maximum humidity 90%, noncondensing

Basic System

- Controller with 15" monitor
- One HSAJet-5000 Print head with automatic ink delivery system
- Product detector & encoder
- Mounting Hardware
- Keyboard with integral trackball

Speed

- 600x600 dpi at 39 m/min
- 600x300 dpi at 78 m/min
- 600x150 dpi at 156 m/min
- 300x600 dpi at 39 m/min
- 300x300 dpi at 78 m/min (one nozzle)
- 300x300 dpi at 156 m/min
- 300x150 dpi at 312 m/min

Inks and Ink System

- 42 ml liter ink supply
- Variety of colors
- Water based inks
- Low level ink detection
- Optional: Large capacity remote bulk

Applications

 Established markets for our printheads include packaging (case coding, bar codes, product marking and labels) and industrial marking.

Software Features of OBJInkDraw

- Windows 95,98,NT,2000
- Simple touch screen user interface
- Fully object oriented, WYSIWG display
- User Interfaces:
- I) Terminal box with graphical display and full keyboard.
- 2) Monitor, keyboard, mouse
- 3) RS232 or Ethernet
- Time: Multiple formats
- Calendar: Multiple formats including Julian date and automatic scheduler
- Counters: Multiple fully programmable
- Roll over hour/minute/second
- Multiple Postdates
- Barcodes: Code 39, I2of5, UPC-A, EAN 13, Code 128, SCC14, US Postal, Data matrix, and many more. Any variable data function can be embedded in barcodes.
- Fonts: All windows based fonts
- Message length 4000 mm (13 ft)
- Graphics: Multiple Windows Bmp files
- Ink Usage: Automatically calculated for each message
- Security: Full featured, password protection. Three locals.
- User Prompts: Unlimited programmable prompts for user input at time of startup.
- Reverse, invert, inverse, mirror, rotate, bolderize, multiple drops, repeat print, ink reduction

Options

Scanners



Productions date: 2002 03 10. Expire date: 2002 03 27

Distributed By:	
i	

HSAUSA, LLC 150 William Street Perth Amboy, NJ 08861 1-800-298-8936 Phone 732-324-0800 Fax 732-324-4488

Email: info@hsausa.com www.hsausa.com