



Ameritek T1000

Tabber/ Labeler/ Stamp Affixer



T1000 (Standard) left to right paper path



T1000 (Optional) right to left paper path

- * ***Heavy duty construction for reliability and durability.***
- * ***Meet all requirements of owner, operator and USPS.***
- * ***Quick and simple job setups.***
- * ***Microprocessor controlled tab placement.***
- * ***Available in both left to right and right to left configurations.***
- * ***Available with product wrap on front (Standard) or rear.***

Ameritek T1000

Tabber/ Labeler/ Stamp Affixer

TECHNICAL SPECIFICATIONS

Configurations

Standard 1½" tabbing head
Left to right or right to left configurations
Available. Also available with product warp
on the rear side of unit.

Speeds

Production Rates based on 8½" product
length.

Single Tab: Up to 20,000 pieces/hour

Double Tab: Up to 15,000 pieces/hour

Triple Tab: Up to 12,000 pieces/hour

Transport Belt: 0 to 300 feet/minute

Tabbing Head: 0 to 300 feet/minute

Product Size

Minimum: 3" x 5"

Maximum: 13½" x 17"

Minimum Thickness: 20 # folded sheet

Maximum Thickness: 3/8"

Tabs/ Labels/ Stamps

Self adhesive on roll with 3" core and
minimum 1/16" gap between tabs, labels,
or stamps.

Minimum Width: ¾" backer width

Maximum Width: 1¾" backer – Standard

Minimum Pitch: ¾"

Maximum Pitch: 4"

Types: tabs, labels, stamps, scratch-offs,
customized stickers, machine grade paper,
clear or translucent.

*Note: Clear and translucent tabs require
an "engineered backer" with printed
registration marking for indexing.*

Roll Size: Up to 13½" diameter mounted
on a 3" core.

Approx. Roll Capacity: 20,000 - 1" tabs or
12,500 - 1½" tabs

Tab Placement

Accuracy: +/- 1/8" repeatability

Physical Size

System Length: 34½"

System Width: 28"

System Height: 38"

Tabletop Height: 8½"

Weight: Approximately 160 lbs.

Electrical Requirements

115 VAC 50/60 Hz @ 5 Amps or

230 VAC 50/60 Hz @ 3 Amps

Ameritek T1000 Table Top Tabber applies tabs, labels, stamps and scratch-offs to a wide variety of media including tri-fold brochures, newsletters, small catalogs and many others. It is designed for professional mailers, commercial printers, fulfillment houses or anyone else requiring a heavy-duty high quality Tabber/ Labeler/ Stamp Affixer.

It has front panel controls that are easy to use, making it simple to set up jobs or to switch between applications.

The Ameritek T1000 can be used inline with most friction feeders, inkjet print systems, conveyors and even some folders. It can also be run offline with a feeder in stand alone operation.



The Ameritek T1000 can also be configured as a Dual Headed Tabber. This system can tab on the leading (toe) and trailing (heel) edges of a booklet in a single pass. The Dual Headed Tabber can run in-line or off-line as a system, or the Tabbers can be unlocked and used as stand-alone units.

**Call us for information and pricing
(800)398-5786**

 **Addresser
Based Systems**

Mailing & Printing Equipment Since 1962

www.addresserbasedsystems.com