



# Ameritek Tabber

Tabber/ Labeler/ Stamp Affixer



*\* High Production Tabbing, Labeling and Stamping.*

*\* Heavy duty construction for reliability and durability.*

*\* Meet all requirements of owner, operator and USPS.*

*\* Quick and simple job setups.*

*\* Microprocessor controlled tab placement.*

*\* Brushless DC Servo employed for unmatched durability.*

*\* Wide Head option available for Post-It-Notes, wide labels, and magnets.*

**TABBING - LABELING – STAMPING**

# Ameritek Tabber

## TECHNICAL SPECIFICATIONS

### Configurations

Standard (2") or Wide Head Systems (4½") available.  
(as defined by the maximum width of backing material)

### Speeds

Production Rates based on 8½" product length.

Single Tab: Up to 30,000 pieces/hour

Double Tab: Up to 24,000 pieces/hour

Triple Tab: Up to 18,000 pieces/hour

Transport Belt: 0 to 600 feet/minute

Tabbing Head: 0 to 375 feet/minute

Application Speeds: Transport belt speeds of 0 to 600 ft/min for tabs < 2" pitch.  
Transport belt speeds of 0 to 375 ft/min for tabs > 2" in pitch.

### Product Size

Minimum: 3" x 5"

Maximum: 13½" x 17"

Minimum Thickness: 20 # folded sheet

Maximum Thickness: 7/16"

### Tabs/ Labels/ Stamps

Self adhesive on roll with 3" core and minimum 1/16" gap between tabs, labels, or stamps.

Minimum Width: ¾" backer width

Maximum Width: 2" backer – Standard  
4½" backer – Wide Head

Minimum Pitch: ¾"

Maximum Pitch: 7"

Types: tabs, labels, stamps, repositionable notes, scratch-offs, customized stickers, machine grade paper, clear or translucent.

*Note: Clear and translucent tabs require an "engineered backer" with printed registration marking for indexing.*

\*\*\* Magnets possible with optional kit.

Roll Size: Up to 19½" diameter mounted on a 3" core.

Approximate Roll Capacity: 40,000 – 1" tabs

### Tab Placement

Accuracy: +/- 1/8" repeatability

### Physical Size

System Length: 37"

System Width: 33"

System Height: 71"

Tabletop Height: 32¾" to 35" - Standard  
35¾" to 38" - Optional

Weight: Approximately 450 lbs.

### Electrical Requirements

115 VAC 50/60 Hz @ 10 Amps or

230 VAC 50/60 Hz @ 5 Amps

The Ameritek Tabber applies tabs, labels, stamps, repositionable post-it notes, and scratch-offs to a wide variety of media including tri-fold brochures, newsletters, small catalogs and many others. It is designed for professional mailers, commercial printers, fulfillment houses or anyone else requiring a heavy-duty high quality Tabber/Labeler/Stamp Affixer.

It has front panel controls that are easy to use, making it simple to set up jobs or to switch between applications.

The Ameritek Tabber can be used in-line with most friction feeders, inkjet print systems, conveyors and even some folders. It can also be run offline with a feeder in stand-alone operation.



The Ameritek Tabber can also be configured as a Dual Headed Tabber. This system can tab on the leading (toe) and trailing (heel) edges of a booklet in a single pass. The Dual Headed Tabber can run in-line or off-line as a system, or the Tabbers can be unlocked and used as stand-alone units.

For More information, call us at

(800)398-5786

[www.addressersbasedsystems.com](http://www.addressersbasedsystems.com)

 **Addresser  
Based Systems**

Mailing & Printing Equipment Since 1962