## Feeder/Dispenser







#### **OVERVIEW**

The S-1750IJ is for production mailing operations that demand maximum throughput from their ink jet printing, labeling, and tabbing bases. The S-1750IJ is an ideal alternative for integrated shuttle feeders and provides superior feeding to precisely separate and singulate many types and sizes of product onto a transport base.

#### **APPLICATIONS**

- Mail Processing
- Ink Jet Bases
- · Labeling Bases
- Tabber Bases
- · Reinforcing Machines

#### TECHNICAL DATA

**Minimum Product Size:** ...... 7.875 W x 3 L in (200 x 76.2 mm) **Belt Speed:** ...... 5700 ipm (144,780 mm/min) Electrical Requirements: 115/230vac, 60Hz, 3A Warranty: ...... Two-year limited

### **FEATURES**

- · Durable steel construction
- · Quality precision parts
- Tool-free adjustments for easy setups and changeovers
- · Advancing gate enables maintenance without stopping a job
- · Variable speed control for synchronous operation
- Run delay (selectable 0-12 seconds)
- · External run input for integrated start/stop control

# **DIMENSIONS** 28 125 in (714 mm) 20.125 in (511 mm) 19 in (483 mm)



103 Osborne Road • Minneapolis, MN 55432-3131 • USA

t 763.502.0000 • f 763.502.0100 • www.streamfeeder.com • E-mail: sales@streamfeeder.com