



Xtreme XM-1 Friction Feeder



Utilities Requirements

115/230vac – 6/3A – 50/60Hz

Product Size

Min. 2"W x 3" L – Max 12"W x 12"L

Product Thickness

Min. .003" – Max. .750"

Product Stack Height

20"

Controls and Interfaces

Simple, pushbutton - Jog, Cycle, Illuminated Reset, Illuminated Stop, Variable Speed, Trigger Delay, End-of-Batch Speed Change, Batch Size Thumb-wheels, External Interface Connection, Trigger Detect Sensor, Miss Detect, optional Auto-Trigger, optional "Hundreds" batch-count, and optional Double Sheet Detect

Xtreme Versatile Feeding Solutions provide dependable and consistent performance for operations pursuing greater productivity through automation. The robust design provides years of service and even maintenance, when required is fast and simple to perform, maximizing uptime and productivity.

Built-in versatility provides the flexibility to process the widest variety of material types, sizes, and thicknesses including sheets, forms, plastic cards, greeting & novelty cards, envelopes, folded documents (including open edge), magazines, brochures, and much more, maximizing return on investment.

Simple, easy-to-use controls and minimal tool-free setup adjustments allow for greater uptime, maximizing productivity.

XTREME Versatile Feeding Solutions are ideal for automatic product feeding for inline multiple feed applications including shrink-wrapping and poly-bagging, or individual offline batch-counting.

The XM-1 is a great value with many standard operating features including miss-product detect and batch-counting.



Batch-counting solution with
Victory BatchDrop



Batch counting solution with
Champion Collection Conveyor



Extended hopper solution with the
XM-100 Bulk Product Feeder



"Roll-around" solution with
Adjustable Mounting Stand

Superior-PHS

9921 - 13th Avenue North
Plymouth, MN 55441

Phone: 763-546-9140

Fax: 763-546-8883

E-mail: info@superior-phs.com

Web: www.superior-phs.com